

60-80 VERSA LIFT WITH 6 COUNTERWEIGHT SLABS

Slab Weight (kg)
2270

Number of Slabs
6

Standard Wheel Base (mm)
3048

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	560	31500	34800	38100	41500	44800
	900	25200	27900	30600	33200	35900
	1200	21500	23700	26000	28300	30600
	1500	18700	20700	22600	24600	26600
	1800	16500	18300	20000	21800	23500
	2100	14800	16400	18000	19600	21100

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	150	29500	32800	36100	39400	42600
	600	22300	24800	27300	29800	32200
	900	19200	21300	23500	25600	27700
	1200	16800	18700	20600	22500	24300
	1500	15000	16700	18300	20000	21700
	1800	13500	15000	16500	18000	19500
	2100	12300	13700	15000	16400	17800
	2400	11300	12600	13800	15100	16300
	2700	10400	11600	12800	13900	15100
	3000	9700	10800	11900	12900	14000

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	21400	23900	26400	28900	31300
	900	18400	20500	22700	24800	27000
	1200	16200	18000	19900	21800	23600
	1500	14400	16100	17700	19400	21100
	1800	13000	14500	16000	17500	19000
	2100	11800	13200	14500	15900	17300

***All Load Capacities are rated with the mast vertical

60-80 VERSA LIFT WITH 5 COUNTERWEIGHT SLABS

Slab Weight (kg)
2270

Number of Slabs
5

Standard Wheel Base (mm)
3048

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	560	27400	30400	33300	36300	39200
	900	22000	24400	26700	29100	31400
	1200	18700	20700	22700	24700	26700
	1500	16300	18000	19800	21500	23300
	1800	14400	16000	17500	19100	20600
	2100	12900	14300	15700	17100	18500

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	150	25600	28400	31300	34200	37100
	600	19300	21500	23700	25900	28100
	900	16600	18500	20400	22300	24100
	1200	14600	16200	17900	19500	21200
	1500	13000	14500	15900	17400	18900
	1800	11700	13000	14400	15700	17000
	2100	10700	11900	13100	14300	15500
	2400	9800	10900	12000	13100	14200
	2700	9000	10100	11100	12100	13100
	3000	8400	9300	10300	11200	12200

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	18400	20600	22800	25000	27200
	900	15800	17700	19600	21500	23400
	1200	13900	15500	17200	18800	20500
	1500	12400	13800	15300	16800	18200
	1800	11200	12500	13800	15100	16500
	2100	10200	11400	12600	13800	15000

***All Load Capacities are rated with the mast vertical

60-80 VERSA LIFT WITH 4 COUNTERWEIGHT SLABS

Slab Weight (kg)
2270

Number of Slabs
4

Standard Wheel Base (mm)
3048

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	560	23400	26000	28500	31000	33600
	900	18800	20800	22800	24900	26900
	1200	16000	17700	19400	21200	22900
	1500	13900	15400	16900	18400	19900
	1800	12300	13600	15000	16300	17600
	2100	11000	12200	13400	14600	15800

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	150	21600	24100	26600	29100	31600
	600	16300	18200	20100	22000	23900
	900	14000	15700	17300	18900	20500
	1200	12300	13700	15200	16600	18000
	1500	11000	12200	13500	14800	16100
	1800	9900	11000	12200	13300	14500
	2100	9000	10000	11100	12100	13200
	2400	8300	9200	10200	11100	12100
	2700	7600	8500	9400	10300	11200
	3000	7100	7900	8700	9600	10400

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	15400	17300	19200	21100	23000
	900	13300	14900	16500	18100	19800
	1200	11600	13100	14500	15900	17300
	1500	10400	11600	12900	14200	15400
	1800	9300	10500	11600	12800	13900
	2100	8500	9500	10600	11600	12700

*****All Load Capacities are rated with the mast vertical**

60-80 VERSA LIFT WITH 3 COUNTERWEIGHT SLABS

Slab Weight (kg)
2270

Number of Slabs
3

Standard Wheel Base (mm)
3048

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	560	19400	21500	23700	25800	28000
	900	15500	17300	19000	20700	22400
	1200	13200	14700	16100	17600	19100
	1500	11500	12800	14100	15300	16600
	1800	10200	11300	12400	13600	14700
	2100	9100	10100	11200	12200	13200

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	150	17600	19700	21800	23900	26100
	600	13300	14900	16500	18100	19700
	900	11500	12800	14200	15600	16900
	1200	10100	11300	12500	13700	14900
	1500	9000	10000	11100	12200	13200
	1800	8100	9000	10000	11000	11900
	2100	7300	8200	9100	10000	10900
	2400	6700	7500	8400	9200	10000
	2700	6200	7000	7700	8500	9200
	3000	5800	6500	7200	7900	8600

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	12400	14000	15600	17200	18800
	900	10700	12000	13400	14800	16200
	1200	9400	10600	11800	13000	14200
	1500	8300	9400	10500	11600	12600
	1800	7500	8500	9500	10400	11400
	2100	6800	7700	8600	9500	10400

*****All Load Capacities are rated with the mast vertical
60-80 VERSA LIFT WITH 0 COUNTERWEIGHT SLABS**

60-80 VERSA LIFT WITH 2 COUNTERWEIGHT SLABS

Slab Weight (kg)
2270

Number of Slabs
2

Standard Wheel Base (mm)
3048

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	560	15400	17100	18800	20600	22300
	900	12300	13700	15100	16500	17900
	1200	10500	11700	12900	14000	15200
	1500	9100	10100	11200	12200	13300
	1800	8100	9000	9900	10800	11700
	2100	7200	8100	8900	9700	10500

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	150	13600	15400	17100	18800	20500
	600	10300	11600	12900	14200	15500
	900	8900	10000	11100	12200	13300
	1200	7800	8800	9700	10700	11700
	1500	6900	7800	8700	9600	10400
	1800	6300	7000	7800	8600	9400
	2100	5700	6400	7100	7800	8600
	2400	5200	5900	6500	7200	7900
	2700	4800	5400	6000	6600	7300
	3000	4500	5100	5600	6200	6700

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	9400	10700	12000	13300	14600
	900	8100	9200	10300	11400	12600
	1200	7100	8100	9100	10000	11000
	1500	6300	7200	8100	8900	9800
	1800	5700	6500	7300	8100	8900
	2100	5200	5900	6600	7300	8100

*****All Load Capacities are rated with the mast vertical**

60-80 VERSA LIFT WITH 1 COUNTERWEIGHT SLAB

Slab Weight (kg)
2270

Number of Slabs
1

Standard Wheel Base (mm)
3048

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	560	11300	12700	14000	15400	16700
	900	9100	10200	11200	12300	13400
	1200	7700	8600	9600	10500	11400
	1500	6700	7500	8300	9100	9900
	1800	5900	6700	7400	8100	8800
	2100	5300	6000	6600	7200	7900

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	150	9700	11000	12300	13700	15000
	600	7300	8300	9300	10300	11300
	900	6300	7200	8000	8900	9800
	1200	5500	6300	7000	7800	8600
	1500	4900	5600	6300	6900	7600
	1800	4400	5000	5700	6300	6900
	2100	4000	4600	5100	5700	6300
	2400	3700	4200	4700	5200	5700
	2700	3400	3900	4400	4800	5300
	3000	3200	3600	4100	4500	4900

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	6400	7400	8400	9400	10400
	900	5500	6400	7200	8100	9000
	1200	4800	5600	6400	7100	7900
	1500	4300	5000	5700	6300	7000
	1800	3900	4500	5100	5700	6300
	2100	3500	4100	4600	5200	5800

***All Load Capacities are rated with the mast vertical

Slab Weight (kg)
2270

Number of Slabs
0

Standard Wheel Base (mm)
3048

Lift Capacities with forks only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from fork face (mm)	560	7300	8200	9200	10100	11100
	900	5800	6600	7400	8100	8900
	1200	5000	5600	6300	6900	7600
	1500	4300	4900	5500	6000	6600
	1800	3800	4300	4800	5300	5800
	2100	3400	3900	4300	4800	5200

Lift Capacities with boom only (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	150	5700	6700	7600	8500	9500
	600	4300	5000	5700	6400	7200
	900	3700	4300	4900	5500	6200
	1200	3300	3800	4300	4900	5400
	1500	2900	3400	3900	4300	4800
	1800	2600	3000	3500	3900	4300
	2100	2400	2800	3200	3600	3900
	2400	2200	2500	2900	3300	3600
	2700	2000	2400	2700	3000	3300
	3000	1900	2200	2500	2800	3100

Lift Capacities with forks & boom (kg)						
		Counterweight extension (mm)				
		0	300	600	900	1200
Load Centre from boom face (mm)	600	3400	4100	4800	5500	6200
	900	2900	3500	4200	4800	5400
	1200	2600	3100	3600	4200	4700
	1500	2300	2800	3200	3700	4200
	1800	2100	2500	2900	3400	3800
	2100	1900	2300	2700	3100	3400

*****All Load Capacities are rated with the mast vertical**